Mainship battery chargers

Charging ahead



Securaplane's battery chargers combine advanced power conversion with established battery charging technology, offering the highest input power quality and value-to-weight-and-size ratio in its class.

Standard production on Gulfstream G350 and G450, CRJ 900 and 1000, Challenger 605 and 800 series, Securaplane chargers reduce battery maintenance while providing significant data for battery and charger maintenance.

Key features

- Patented charging method
 Battery receives the optimum amount of charge for any temperature condition and state of charge.
- Reliability
 Proven high-reliability fan improves charger reliability, while significantly decreasing weight and volume.
- Fault storage
 Charger stores every detected fault in permanent memory to eliminate the guesswork in identifying and solving battery/charger system problems.
- Alpha-numeric display
 Status and faults shown on self-contained eight-character display

Models and applications

- BC-1302
 DC-10, MD-11, MD-10
- BC-1305
 DC-9, MD-80 series
- BC-1306, BC-1309

 Bombardier CRJ series,
 Challenger 605 and 800 series
- BC-1307
 Gulfstream 350/450
- BC-1311 Gulfstream 650

Securaplane



Mainship battery chargers

Charging ahead

Specifications

Application	DC-9, MD-80 series	DC-10, MD-11, MD-10	Bombardier CRJ series, Challenger 605 and 800 series	Gulfstream 350/450	Gulfstream 650
Model	BC-1303, BC-1305	BC-1302	BC-1306, BC-1309	BC-1307	BC-1311
Part no	100-1059-01 (BC-1303) 100-1042-01 (BC-1305)	100-0212-01	100-1084-01 (BC-1306) 100-2668-01 (BC-1309	100-1104-01	100-1311-01
Dimensions	5.51"x 4.95"x 9.1"	5.51"x 4.95"x 9.1"	4.3"x 4.9"x 8.9"	4.3"x 5.6" x 9.9"	4.3"x 5.6" x 9.9"
Weight	7.5 lbs	7.5 lbs	5.1 lbs	5.5 lbs	5.5 lbs
Connectors	MS27335T14A18PMS3452W20-14P	MS85528/2-22-A01-ABussmann C2808-1Bussmann C4044	MS27335T14A18PMS3452W20-14P	MS27335T14A18PMS3452W20-14P	MS27335T14A18PMS3452W20-14P
Input power requirements [All models]	 Aircraft 115VAC 3 Phase 400 HZ [102-124 VAC Operating] Efficiency 85%-89% Low input power distortion 				
Maximum output (All models)	40 Amps at 30V36VDC at 33A				
Battery types supported	Ni-CadULM Ni-CadHawker sealed lead acid (BC-1305 only)	Ni-Cad ULM Ni-Cad	Ni-CadULM Ni-CadHawker sealed lead acid	• Hawker sealed lead acid	Securaplane Li-ionNi-CadULM Ni-CadHawker sealed lead acid

Alpha-numeric LED display

BC-1300 series chargers incorporate an eight-character LED display to communicate charger and battery system status at a glance.

Charger faults

Fan speed CPU Temperature Voltage Current Power Stored fault history

Battery faults

Abnormal temperature Temperature sensor circuit Cell unbalance sensor unit

LED display

Eight-character alphanumeric

Diagnostics

Self test
Output voltage
Output current
Operating hours
Temperatures
Power

Time

Date

Software revision

Charge mode

Bulk charge mode Topping charge mode Trickle charge mode



Securaplane

12350 N Vistoso Park Road Oro Valley AZ 85755 USA Tel: +1 (520) 297 0844 Fax: +1 (520) 498 4924 www.securaplane.com www.meggitt.com

